

BRIGHTWELL

Datasheet



Ecosink 2 Chemical Datasheet

Ecosinka is a chemical dispenser for use with three compartment sinks in commercial kitchens. It is available with BrightGap and AirGap backflow preventers. Ecosink dispenses two chemicals with an option to choose a single or dual water supply.



Technical specifications

Dimensions (mm) (H x W x L)	258 x 142 x 80
Weight	2.5 kg
Branding	Multi-coloured chemical labels available
Installation	Working temperature range 4 - 82 C Working pressure range 2 - 5 bar Minimum water flow required: 8.5L/min
Dilution	13 independent dilution ratios 6:1 - 695:1
Material	Cover: Stainless Steel Connector Bracket: Polypropylene Valve Switch Dial: Polypropylene



	Ball Valve and Inlet Connectors: Brass Proportioner Dilution Seal: EPDM/Viton Venturi Assembly: Polypropylene
Operation	Simple twist and lock on/off application
Accessories	Hanging bracket Secure chemical cabinet
Approvals	ASSE: Record Number:1562
Warranty	1 year

Adjustable dose between 5ml and 30ml for use with concentrated chemicals. Max: 150CPI

In the box

High flow 1.5m outlet tube with flood ring

Clear PVC chemical suction tube

Ecosink 2 chemical dispenser unit

Screw pack

Foot filter

Ceramic weight

Instruction manual and chemical labels

Part numbers

Part number	Description
DS1HC1HC-S	EcoSink 2 Chemical, Single Water, Highflow, BrightGap
DS1HC1HH-S	EcoSink 2 Chemical, Dual Water, Highflow, BrightGap

BESPOKE PART NUMBERS AVAILABLE ON REQUEST

Shipping info



Shipping method	Quantity of units	Dimensions L x W x H (cm)	Net packed weight (kg)
Unit	1	32 X 27 X 16	2.55
Case	8	65.5 X 54.5 X 35	22
Pallet	160	131 X 110 X 190	455

BESPOKE PACKAGING AVAILABLE ON REQUEST

BRIGHTWELL

Brightwell Dosing Ltd
Unit 1, Rich Industrial Estate
Avis Way, Newhaven
East Sussex, BN9 0DU

T: +44 (0)1273 513 566
E: sales@brightwell.co.uk

© 2024 Brightwell Dosing Ltd | Registered in England, Number 00661996.

