



DESCRIPTION

WashBasic L is the new peristaltic pump that renews the look and the functionality of SEKO single pumps. Fixed speed peristaltic pump with digital adjustment of delay, dosing and lock-out time. Suitable for wash extractor up to 30 kg.

Comes equipped with 2 cables:

- cable 1 for the 100÷240 Vac power supply
- cable 2 dedicated to receiving a 20÷240 Vac signal that activates the dosing cycle.

FEATURES

- **Precise programming** of delay, dosing and lock out times by keys display and microprocessor technology
- **Long lifetime** of **squeeze tube** and motor due to latest Tubing technology
- **IP 65** enclosure for optimum water resistance. SEKO's material and construction offers excellent resistance to impact and chemical exposure
- **Electrical class 2**, no ground wire needed
-

TECHNICAL SPECIFICATIONS

Power supply	100÷240 Vac @ 50/60 Hz
Power consumption	5 W
Squeeze tube	SekoFlex
Pressure	max 0,1 bar (1.5 psi)
Flow rate	250 ml/min (8.4 oz/min)
Delay time	0÷999 seconds
Dosing Time	0÷999 seconds
Lock-out time	0÷999 minutes
Class of protection	IP 65 (NEMA 4X)
Dimensions (L x H x D)	127 x 102 x 113 mm (5" x 4" x 4.4")
Operating Temperature	+10÷50°C
Storage Temperature	-20÷60°C